

**Rolls Powered Bonanza Performance Data (+2 ISA)**

<b>Altitude Feet</b>	<b>Torque Ft-lbs</b>	<b>TOT °C</b>	<b>Fuel Flow PPH</b>	<b>TAS Kts</b>	<b>Endurance NM / P</b>
3,000	72	640	194	173.9	0.90
4,000	71	650	193	177.8	0.92
5,000	71	650	190	182.4	0.96
6,000	72	680	188	184.4	0.98
7,000	72	665	186	187.5	1.01
8,000	72	665	184	189.5	1.03
9,000	71	675	183	189.4	1.03
10,000	71	685	181	190.3	1.05
11,000	72	690	179	192.1	1.07
12,000	72	690	177	194.3	1.10
13,000	72	700	176	196.5	1.12
14,000	72	710	175	198.3	1.13
15,000	72	720	175	199.9	1.14
16,000	72	730	173	200.9	1.16
17,000	72	740	173	202.9	1.17
18,000	72	750	171	204.9	1.20
19,000	68	740	164	201.6	1.23
20,000	65	740	155	201.8	1.30
21,000	63	740	150	202.1	1.35
22,000	60	740	145	202.7	1.40
23,000	58	740	140	201.9	1.44
24,000	57	740	134	201.0	1.50